

✓ OK  
✗ not OK

1 ✓

2 ✗

3 ✓

4 ✗

5 ✓ (max. 280 °C / max. 536 °F)

6 ✗

7 ✗

8 ✗

9 ✓

10 ✗

11 ✓

12 ✗

13 ✗

14 ✗

15 ✗

16 ✓

17 ✓

18 ✗

19 ✗

20 ✓

21 ✓

22 ✓

23 ✓

24 ✗

25 ✓

1 ✗

2 ✓

3 1x

4 ✓

5 ✗

6 ✗

60 °C / 140 °F

> 2 h

BLANCO ACTIV Pulver

Art.-No.: 520 784

Art.-No.: 520 523

BLANCO GmbH + Co KG  
Service  
Tel.: +49 7045 44-81 419  
info@blanco.de  
www.blanco-germany.com

## BLANCO

281379 - 07/2017



## BLANCO SILGRANIT®





✓ OK

✗ not OK



	+1 mm / -1 mm		+2 mm / -1 mm				+0,5 mm F	
	C [mm]	A [mm]	B [mm]	R1 [mm]	D [mm]	E [mm]	R2 [mm]	F [mm]
BLANCO ALAROS 6 S-F	+270	1150	500	26	1140	490	21	9
BLANCO AXIA III 45 S-F	+10	772	502	21	760	490	15	7
BLANCO AXIA III 5 S-F	-15,5	907	502	21	895	490	15	7
BLANCO AXIA III 6 S-F	-15	992	502	21	980	490	15	7
BLANCO AXIA III XL 6 S-F	-15	992	502	21	980	490	15	7
BLANCO DALAGO 45-F	-3	457	502	16	445	490	15	9
BLANCO DALAGO 5-F	-3	507	502	16	495	490	15	9
BLANCO DALAGO 6-F	-3	607	502	16	595	490	15	9
BLANCO DALAGO 8-F	-3	807	502	16	795	490	15	9
BLANCO ELON XL 6 S-F	-16	772	492	16	760	480	15	9
BLANCO METRA 45 S-F	-3	772	492	16	760	480	15	9
BLANCO METRA 5 S-F	-3	852	492	16	840	480	15	9
BLANCO METRA 6-F	-3	607	492	16	595	480	15	9
BLANCO METRA 6 S-F	-3	992	492	16	980	480	15	9
BLANCO METRA 9-F	-10	852	492	16	840	480	15	9
BLANCO METRA XL 6 S-F	-3	992	492	16	980	480	15	9
BLANCO NAYA 6-F	-2,5	606	501	16	595	490	15	9
BLANCO NAYA 8-F	-2,5	806	491	16	795	480	15	9
BLANCO NAYA XL 9-F	-30	851	501	16	840	490	15	9
BLANCO PLEON 6-F	-2,5	607	502	16	595	490	15	9
BLANCO PLEON 8-F	-60	692	502	16	680	490	15	9
BLANCO PLEON 9-F	-30	852	492	16	840	480	15	9
BLANCO ZENAR 45 S-F	+14	849,5	499,5	16	840	490	15	9
BLANCO ZENAR 5 S-F	+14	904,5	499,5	16	895	490	15	9
BLANCO ZENAR XL 6 S-F	-16	989,5	499,5	16	980	490	15	9
BLANCO ZENAR XL 6 S-F DGP	-16	989,5	499,5	16	980	490	15	9
BLANCO AXIA II 45 S-F	+26							10
BLANCO AXIA II 5 S-F	+6							10
BLANCO AXIA II 6 S-F	+6							10
BLANCODELTA II-F	-19							9



www.blanco-germany.com

