



Type	Width [mm]	Height [mm]	Depth [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power (75/65/20 °C) [W]	Power (75/65/24 °C) [W]	Power (55/45/24 °C) [W]	Electric heater maximal power [W]
	W	H	D	C	B	A							
QB-612	595	1185	101-106	50	53-58	525	1,15	16,3	5,3	586	528	260	300
QB-617	595	1698	50	53-58	525	1,70	23,2	7,8	849	765	375	600	



Vertical manifolds:



Finish and guarantee:

- standard: phosphatizing + polyester-epoxy lacquer; 5 year guarantee;
- on request: electrophoresis + polyester-epoxy lacquer; 10 year guarantee;

Mounting brackets:

- set for assembly on the wall
- brackets in the colour of a towel rail

Valve:

- integrated, hidden under cover;
- thermostatic valve included

Heater :

for a separate order - page 24

Working pressure:

4 bars

Maximal temperature:

95 °C

Connections:



- inner threads G 1/2
- air-vent plug G1/8 hidden behind

Remarks:

- water inlet at the left side
- thermostatic head in chrome

